



DE

EN

FR

CS


SK

PL

ES

Operation Manual

Easy Sun PARASOL Sunshade



Introduction

SUN GARDEN offers you, with the *Easy Sun* PARASOL Sunshade, a high quality technically advanced and long-lasting product. It is constructed to the current technological state of the art and recognised safety standards. The following operation manual should help you to enjoy using your sunshade for a long time ahead.

This operation manual applies both to the 4-cornered and 8-cornered version of the sunshade, as the only difference between the sunshades is the shape of the sunshade frame and the canopy. Many sketches in the operation manual show the 8-cornered version of the sunshade. They are used for clarity and can equally be applied to the 4-cornered version. All operation and working sequences are identical for both versions.

The manual contains information about the following topics:

- Safety
- Installation
- Operation
- Care

Please read the operation manual carefully before using the sunshade. Damages caused by non-observance of the instructions are excluded from any liability and guarantee.

The sunshade has been designed as protection from the sun, and is intended for this use only. **Use the sunshade only**

- for its intended use as a sunshade
- in a technically correct condition

Malfunctions, which could influence the safety and function of the sunshade must be rectified immediately.

All repairs described in the manual can be carried out by the user. Any further complicated repairs should not be carried out by the user. The repair information is intended for those persons who are competent to use the tools described safely. Only carry out this repair work using suitable tools.

SUN GARDEN GmbH · Emsdettener Str. 233 · D-48485 Neuenkirchen · www.sun-garden.de · +48 (63) 289 89 00

We reserve the right to make alterations without prior notice due to technical improvements. The following manual may neither be reprinted or copied without the prior consent of SUN GARDEN.



www.tuv.com
ID 1111210102



1. Safety information	2	8. Operating the sunshade	14
1.1 Important symbols	2	8.1 Opening the sunshade	14
1.2 Safety information	3	8.2 Adjusting the sunshade inclination	15
2. Type supplied and included in delivery	3	8.3 Closing the sunshade	15
3. Sunshade construction	4	8.4 Rotation of the umbrella on its axis.	16
4. Fittings	5	9. Pulling on the protective cover	17
4.1 General	5	10. Care of your Easy Sun Parasol sunshade	17
4.2 Nameplate	5	10.1 Cleaning the canopy material	17
4.3 Canopy material	5	10.2 Removing sunshade cover	18
4.4 Sunshade frame	6	10.3 Impregnating the canopy material	19
4.5 Operating elements: the winch handle	6	10.3 Cleaning the sunshade	19
4.6 Operating elements: the block	6	11. Storage	19
4.7 Sliding tube stop	7	12. Maintenance	20
4.8 Swivel foot	7	12.1 Periodical maintenance	20
4.9 Protective cover	7	12.2 Yearly maintenance	20
5. Sunshade space requirements	8	13. Service Centre/ spare part supply	21
6. Setting up the sunshade	11 -13	14. Storage	21
7. Fitting the winch handle	13	15. Specifications	21
		16. Guarantee	22
		Guarantee certificate	23

1. Safety information

1.1 Important symbols

Special information is labelled with the following graphics in the manual:



Caution!

This symbol identifies information which refers to danger of injury and accident.



Note

This symbol identifies general tips for handling.



Note

This symbol identifies information which can avoid damage to the sunshade.

1.2 Safety Information



Caution: Tipping hazard!

- Only set the sunshade up on firm foundations.
- Always ensure that the Parasol base is firmly seated.
- Always close the sunshade and put the cover on if the wind rises above a „moderate breeze“, if there is snowfall or if it is raining.
- Do not use your parasol on roof top terraces.

Wind strength description (Beaufort scale):

“Moderate breeze” = Beaufort force 4 Bft

Effects on land = twigs and small branches move, paper and dust is raised

Effects on sea = small, but long waves, more white Caps.

- Do not hang any objects (e.g. clothing) on the sunshade frame.



Caution: Risk of accidents!

- Before opening the sunshade ensure that no persons are present in the opening area and before closing the sunshade ensure that no persons are present below the sunshade.
- The sunshade is not a toy!
Ensure that children do not use either the sunshade, the canopy or the base for playing or climbing.



Caution: Fire hazard!

Do not use open fire (e.g. garden barbecue or grill) beneath or right next to the sunshade.



Caution: Risk of injury!

Only carry out repairs to your sunshade when you are competent to use the tools required safely.

2. Type supplied and included in delivery



Note

All our products undergo rigorous testing for quality and completeness before delivery. Check the contents of the packaging before starting assembly. If any components are missing or faults can be seen please contact your dealer. If possible you should keep the packaging for any guarantee work which may be necessary.


The sunshade is delivered in stable cardboard packaging.

Dimensions: 2490x 605 x 225 mm (98" x 23.8" x 8.86")


Total weight: 24,8 kg (54,6 lbs.)

The following components are contained in the packaging:

- 1 Sunshade - 1 piece
- 2 Swivel insert - 1 piece
- 3 Winch handle - 1 piece
- 4 Allen key; Size 4 mm - 1 piece
- 5 Operation manual - 1 piece
- 6 Standard protective cover - 1 piece
- 7 Sliding tube stop - 1 piece
- 8 Screws 3.9x9.5 mm - 5 pieces
- 9 Positioner - 1 piece



3. Sunshade construction



* The Parasol Stand/ Parasol Base base is **NOT** included in delivery with the sunshade (optional extra).

4. Fittings

4.1 General

Material such as plastic, plastic coated aluminium and non-rusting steel have been used for all mechanical components of the sunshade. This enables the sunshade to have a very high degree of weather resistance, functionality and service life.

4.2 Nameplate


The nameplate is attached to the stand tube in the vicinity of the lower slider tube stop. The following information is printed on the nameplate:

Sunshade model

Manufacturer

Manufacturer's address
with internet address

Sticker with Serial No.



4.3 Canopy material

The canopy material is manufactured in Polyester fabric or Polypropylene depending on the version. Both fabric types are treated to be water-repellent. Coloured canopies are tested for light and colour fastness (DIN 54 004).

The canopy material can be removed from the sunshade easily for cleaning. Please observe the information in the chapter entitled "Care".



Note


The sunshade canopy material is treated to be water-repellent. This treatment is however not intended to prevent water penetration in heavy rainfall.

The *Easy Sun* PARASOL is not an umbrella.



4.4 Sunshade frame


The sunshade frame is used to tension the canopy material. It consists of the frame arms and two frame seats. The canopy material is fixed to the sunshade frame with velcro bands and screws. Opening the frame is done by a cable which is operated by the winch handle.



4.5 Operating elements: the winch handle

The winch handle, manufactured in stainless steel, is used to open and close the sunshade. Handling is improved by the winch handle having a rotating handle on bearings.


The winch handle length is designed so that the sunshade can be opened or closed without needing too much strength..



4.6 Operating elements: the bottom clamp


The sunshade sliding tube is held in the required position by the bottom clamp.

After loosening the locking screw the sunshade inclination can be altered and adapted to the angle of the sun.



4.7 Sliding tube stop

The sliding tube stops limit the sunshade inclination. They prevent the sunshade being adjusted to too great an inclination.



4.8 Swivel insert

The swivel insert is mounted in the lower part of the stand tube.


It allows positioning of an sunshade around its axis (360°). Adjustment is performed with the locking pin positioning.

Instructions on how to use the rotation feature is provided in Section 8.4 (page 16).



Caution:


- Before removing the sunshade from the base, it is necessary to lock the function of rotation.



4.9 Protective cover

The protective cover, made of weather-resistant PE fabric, protects the sunshade from damage to the frame arms and the canopy material in any weather.


Despite this the sunshade should not be left out in the open in extreme weather conditions such as storms or heavy frost, but should be kept in a dry and protected location.



5. Sunshade space requirements 350/8 or 320x320


When selecting the location for your *Easy Sun* PARASOL sunshade make sure there is enough space between it and any nearby buildings, trees etc.

The following sketches show you the space required by an opened sunshade.




Sunshade space requirements Oval 365x275

When selecting the location for your *Easy Sun* PARASOL OVAL sunshade make sure there is enough space between it and any nearby buildings, trees etc. The following sketches show you the space required by an opened sunshade.



Sunshade space requirements XL 375/8 or Curve 350/8

When selecting the location for your *Easy Sun* PARASOL sunshade make sure there is enough space between it and any nearby buildings, trees etc. The following sketches show you the space required by an opened sunshade.



6. Setting up the Sunshade




Caution: *Danger of accident!*


It is easier if you can get a second person to help when setting up the sunshade.

Ensure that the Parasol base is secure and stable before setting up the sunshade.

- **A** Remove the swivel insert from bottom clamp.




- **B** Slide the Stand tube into the bottom clamp.



- **C** Push the stand tube away to install the positioner.


- **D** Fasten the positioner using a screwdriver.

- **E** Fasten the sliding tube stop part using a screwdriver.




6. Setting up the Sunshade


- F Align the stand tube in the top block so that the positioner part can be insert inside the opening between the two tubes



- G Fasten the top block to the stand tube using a screwdriver.



- H Slide the swivel insert inside the stand tube (with the positioning pin pulled out). Once the swivel insert is in place turn the positioning pin to lock the swivel insert.



6. Setting up the Sunshade



Caution: *Danger of accident!*

It is easier if you can get a second person to help when setting up the sunshade.

Ensure that the Parasol base is secure and stable before setting up the sunshade.


- Place the sunshade with its stand tube into the stand tube seat of the Parasol base.
- Push the stand tube in as far as the stop in the stand tube seat.
- Turn the sunshade backwards and forwards until the floor sleeve engages in the stand tube seat (centred).



Note

If the floor sleeve has engaged correctly, the sunshade can no longer be turned.

- Clamp the sunshade by tightening the union nut in the stand tube seat.




7. Fitting the winch handle

- Place the winch handle in the location hole so that the recess in the handle is facing the grub screw.
- Tighten grub screw. When tightening, ensure that the grub screw engages exactly into the recess.
- Loosen grub screw with Allen key (SW 4 mm, 0.15").



Note

Overtightening of the grub screw causes damage to the Allen screw.




8. Operating the sunshade

8.1 Opening the sunshade




Caution: Danger of accident! Ensure that no persons or objects are in the vicinity of the opening area before opening the sunshade.


- Ensure that no persons or objects are in the vicinity of the opening area before opening the sunshade.
- Push the sunshade sliding tube to the upper stop and secure by tightening the locking screw.



- Open the sunshade by turning the winch handle in a clockwise direction (OPEN).




To prevent the possibility of wind induced damages to the parasol, please fully open the canopy by engaging the crank system, making sure the brake fully locks in. The lower hub needs to press up against the glide tube to have brake fully engaged. If there is a gap, canopy is not stable.



8.2 Adjusting the sunshade inclination

- Loosen the clamp locking screw.
- Push the sunshade sliding tube to the required position and secure by tightening the locking screw.




8.3 Closing the sunshade Caution:



Danger of accident!

Before opening or closing the sunshade ensure that no persons or objects are under the sunshade.


- Close the sunshade by turning the winch handle in an anticlockwise direction (CLOSE).



! Note

- To avoid water stains you should only close the sunshade in a dry condition and use the protective cover. **If the sunshade is closed when wet, open it as soon as possible and let it dry out.**

- Loosen the clamp locking screw.
- Push the sunshade sliding tube down as far as the lower stop.
- Secure by tightening the locking screw





8.4 Rotation of the umbrella on its axis

- ❶ Release the lock by pulling out the knob pin and rotate it 90°.
- ❷ Place the umbrella in the desired position.

! Note

- Rotate the umbrella only when the canopy is closed and secured against the tube using a belt or if the canopy is open and at 45° to the surface.



- ❸ Lock the umbrella by turning the pin 90°. For safety reasons turn the umbrella slightly until a click of the lock can be heard.




Note

If the floor sleeve has engaged correctly, the sunshade can no longer be turned.



Note

- Place the pin in locked position before removing the umbrella from the base.



9 . Pulling on the protective cover

The sunshade and canopy material should be protected against soiling and damage by pulling on the protective cover when not in use.

When doing this use a stepladder and get help from a second person.




Caution: Danger of accident!

Only set the stepladder up on firm foundations. Get a second person to hold the stepladder to prevent accidents.

- Pull the protective cover over the sunshade from the top.
- Close the protective cover by looping the closing tape around the sunshade and knotting it.

Protective cover

Closing tape



A protective cover with a sawn in rod and a long rope can be purchased as well. This particular protective cover can be pulled over the parasol without the use of a ladder. The Polyester based protective cover is washable, weather resistant and fits perfectly. The cover is available in many colors and it can be attached directly to the parasol in an especially for that purpose designed bag, which is included with the cover.



10. Care of your *Easy Sun* PARASOL SUNSHADE



Note

- Do not use any sharp-edged tools such as knives or metal scrapers, or any aggressive cleaners or solvents, to clean your sunshade.
- Do not use large quantities of water when cleaning, in other words do not use hosepipes or high-pressure cleaners.

10.1 Cleaning the canopy material

The canopy material can be cleaned of dust and light soiling using a brush or a damp cloth.

If heavy soiling is present the canopy must be removed from the sunshade frame and cleaned. You can find information about cleaning the canopy material on the label sewed onto the canopy.




10.2 Removing sunshade cover

Tools required:
Phillips screwdriver No. 2


Stages:

- Open the sunshade about half-way.
- Release all material velcro bands on the sunshade frame from the inside.



- Close sunshade and remove all screws in the sunshade cover bottom fixing with a Phillips screwdriver.
- Open zip and closing tape in top cover fixing and remove cover downwards from sunshade frame.

Reassembly of the canopy material takes place in the same manner but in reverse order




10.3 Impregnating the canopy material

The canopy material must be impregnated with water-repellent material after cleaning. You can use any commercially available impregnating material.

! Note

- Only use impregnating materials suitable for the material in your canopy. Observe the instructions for use provided with the impregnator.



10.4 Cleaning the sunshade

Clean all plastic and aluminium components with a damp cloth.

You can best remove heavy soiling with a mild cleanser free of scouring agents.

! Note

- To avoid damage to component surfaces please observe the instructions for use provided with the cleanser.



11. Storage

All sunshade and floor stand components must be stored in a dry and frost-free location during long periods of non-use and over the winter months.



Note

To avoid water stains you should only fold down your *Easy Sun* PARASOL sunshade, cover it with the protective cover and store it in a dry condition. If possible you should use the original sunshade packaging for storage.

Storing the sunshade:

- Clean the stand, sliding tube, canopy material and protective cover.
- Allow the canopy material and protective cover to dry thoroughly.
- Pull on the protective cover and store the sunshade.


12. Maintenance

12.1 Periodical maintenance

The sliding areas of the stand and slide tube should be cleaned with a damp cloth. Dust and dirt in this area can lead to difficulty in adjusting the inclination and to damage to the tube surface.

12.2 Yearly maintenance

You should carry out a thorough inspection of your sunshade using the following checklist, either after the first assembly or before storing the sunshade over longer periods.



Checklist *Easy Sun* PARASOL sunshade:

Test	NOT in working order
Check canopy material for damage	Replace canopy material ²
Check block function (function see chapters 4.6 and 8.2)	Replace block ¹
Check winch handle for damage	Replace winch handle ¹
Check sliding tube stops for damage	Replace sliding tube stops ¹
Check winch handle function (smooth running)	Replace drum axle ¹
Check brake function (when opening or closing the sunshade must remain stable in any position)	Replace winch housing cover ¹
Check sunshade frame for damage	Replace frame arm ¹
Check sunshade frame seat (see chapter 4.4)	Replace frame seats ¹
Check floor sleeve for damage (see chapter 4.8)	Replace floor sleeve ¹
Give the whole sunshade a visual check	Replace damaged components ¹

1) Call Service Centre

2) See care chapter


13. Service Centre / Spare

If you have any questions about setting up, require our repair service or wish to order spare parts, please contact one of our Service Centres (see Service Centre / ordering spare parts information sheet) or visit our Internet site at www.sun-garden.de.

14. Disposal

The sunshade consists of metal and plastic components. You should dispose of any of these materials in accordance with the regional or national environmental and disposal regulations.

If you have any questions about disposal, please contact your local authority or one of our service centres (see information sheet entitled Service centres / spare parts disposal).



15. Specifications

Total height (H):

sliding tube retracted = approx. 2950 mm (9.7 ft.)

sliding tube extended = approx. 3050 mm (10.0 ft.)

Clear head (Hd)

height = approx. 2050 mm (6.7 ft.)

Depth (T) / closed:

Parasol base = approx. 1200 mm (3.95 ft.)

Bottom pole = approx. 1000 mm (3.3 ft.)

Depth (T) / opened / 4-cornered version:


Parasol base = approx. 4100 mm (13.5 ft.)

Bottom pole = approx. 3850 mm (12.6 ft.)

Depth (T) / opened / 8-cornered version:

Parasol base = approx. 4100 mm (13.5 ft.)

Bottom pole = approx. 3850 mm (12.6 ft.)



Width (B) / closed:

Parasol base = approx. 880 mm (2.9 ft)

Bottom pole = approx. 500 mm (1.65 ft.)

Width (B) / opened:

4-cornered version = approx. 3200 mm (10.5 ft.)

8-cornered version = approx. 3250 mm (10.65 ft.)

Canopy material dimensions:

4-cornered version (De^2) = approx. 3200 mm (10.5 ft.)

8-cornered version (Dr) = approx. 3500 mm (11.5 ft.)

Stand and sliding tube diameters = approx. 70 mm (2.76")

Weight:

complete sunshade = approx. 19.00 kg (42.2 lbs.)


Weight / canopy:

Polyester - 4-cornered version = approx. 1.85 kg (4 lbs.)

Polyester - 8-cornered version = approx. 1.65 kg (3.6 lbs.)

Polypropylene - 4-cornered version = approx. 2.40 kg (5.3 lbs.)

Polypropylene - 8-cornered version = approx. 2.10 kg (4.6 lbs.)



16. Guarantee

Sun Garden GmbH, Emsdettener Straße 233, 48485 Neuenkirchen, gives a product guarantee of two years on the basis that Sun Garden GmbH will replace or repair, as they see fit, parts which have become defective due to material or production faults.

The following are excluded from the guarantee:

- Damages which occur as a result of non-observance of the assembly or operating manuals or of unauthorised repairs.
- Products from which the fabrication number has been removed or destroyed.
- Damages arising due to acts of God.
- Wind damage is not covered under the warranty.

The guarantee certificate, completely filled out, and proof of purchase (till receipt) is required for proof of guarantee claims.

The guarantee becomes active on the day of purchase.

Please proceed as follows to process any guarantee claims arising:

- Fill out the guarantee certificate completely, including a short description of any faults.
- Provide your proof of purchase with the guarantee certificate.
- Bring the complete item (individual components see „Included in delivery“) back to your dealer, who will then deal with your guarantee claim.

This guarantee does not restrict the purchaser's defective goods rights with respect to post-fulfilment, repudiation, reduction or damage compensation against the seller.



Note

Please use the original packaging to transport the article if possible to avoid any further damage.

Guarantee certificate



Angaben des Typenschildes:

Purchaser's address:

Model: _____

Fabrication-No.: _____

Date of Purchase: _____

Dealer's adress:

Dealer's stamp and signature:

Short description of faults:

Pictures of the damage may be required in some cases.

DE - SUN GARDEN GmbH · Emsdettener Straße 233 · D-48485 Neuenkirchen · www.sun-garden.de · +48 (63) 289 89 00
USA - Sun Garden USA - 262 Quarry Road Unit J - Milford, CT 06614 - 800-403-2120
Canada - Sun Garden Canada - 100 Four Valley Drive Unit A, Concord, ON L4K4T9 - 888-727-8121
Poland - Sun Garden Poland - 62-709 Malanów , ul. Turecka 36 - +48 (63) 289 89 00

